

**AMENDMENT TO THE CLAIMS**

Claims 1-33. (canceled)

Claim 34. (New) An image pickup system comprising a commander, a video camera and a display device;

wherein said commander includes:

command information storing means for storing a plurality of kinds of command information;

command information generating means for generating a plurality of kinds of command information which correspond to a plurality of different operations performed by a user, the generation of the command information being carried out on the basis of said plurality of kinds of command information which are stored in said command information storing means; and

transmitting means for transmitting said command information as transmitted information;

wherein said video camera includes:

image pickup means for obtaining an image pickup signal by imaging an object;

receiving means for receiving said transmitted information;

recording and reproducing means for recording and reproducing said image pickup signal to and from a recording medium;

image information storing means for storing a plurality of kinds of image information;

display-ready video signal generating means for generating a display-ready video signal by combining either of the image pickup signal obtained by said image pickup means or the image pickup signal reproduced from said recording medium by said recording and reproducing means and said image information;

transmitting means for transmitting said display-ready video signal; and

controlling means for controlling said image pickup means, said recording and reproducing means and said display-ready video signal generating means in accordance with any one of a plurality of operation modes; and

wherein said display device includes:

receiving means for receiving said display-ready video signal transmitted from said transmitting means of said video camera; and

displaying means for displaying an image represented by the received display-ready video signal.

Claim 35. (New) The image pickup system according to claim 34, wherein said video camera and said display device are separate entities.

Claim 36. (New) The image pickup system according to claim 34, wherein said display device is shaped to be worn on the head of the user.

Claim 37. (New) The image pickup system according to claim 34, wherein said commander and said video camera are separate entities.

Claim 38. (New) The image pickup system according to claim 34, wherein said video camera, said display device and said commander are separate entities.

Claim 39. (New) The image pickup system according to claim 34, wherein a signal transmission is performed by a wireless transmission system between said transmitting means of said commander and said receiving means of said video camera, and between said transmitting means of said video camera and said receiving means of said display device.

Claim 40. (New) The image pickup system according to claim 34, wherein said image information storing means stores a plurality of kinds of image information constituting a graphic user interface capability.

Claim 41. (New) The image pickup system according to claim 34, wherein, in accordance with the operation mode, said controlling means controls said display-ready video signal generating means to generate said display-ready video signal by use of different kinds of image information read from said image information storing means and said image pickup signal obtained by said image pickup means.

Claim 42. (New) The image pickup system according to claim 41, wherein said plurality of operation modes include a standby mode in which images based on the image pickup signals obtained by said image pickup means are displayed on said displaying means but in which said image pickup signals are not recorded to said recording medium, and a recording mode in which the images based on said image pickup signals obtained by said image pickup

means are displayed on said displaying means and in which said image pickup signals are recorded to said recording medium.

Claim 43. (New) The image pickup system according to claim 42, wherein at least a part of said image information constitutes a graphic user interface capability which is not used in said recording mode but used in said standby mode.

Claim 44. (New) The image pickup system according to claim 34, wherein said plurality of operation modes include a recording mode in which the images based on said image pickup signals obtained by said image pickup means are displayed on said displaying means and in which said image pickup signals are recorded to said recording medium and an edit mode in which the image pickup signals recorded on said recording medium are edited.

Claim 45 (New) The image pickup system according to claim 44, wherein at least a part of said image information constitutes a graphic user interface capability which is not used in said recording mode but used in said edit mode.

Claim 46. (New) The image pickup system according to claim 40, wherein said display-ready video signal generating means generates a pointer constituting part of said graphic user interface capability on the basis of said image information.

Claim 47. (New) The image pickup system according to claim 46, wherein said controlling means moves said pointer within a frame on the basis of the signal received by said receiving means of said video camera.

Claim 48. (New) The image pickup system according to claim 46, wherein said commander includes moving state detecting means for detecting self-movements of the commander brought about by the user, and wherein said command information generating means of said commander generates command information based on the movements detected by said moving state detecting means.

Claim 49. (New) The image pickup system according to claim 47, wherein, upon receipt of a signal including a predetermined command transmitted from said commander, said controlling means moves said pointer only unidirectionally on the basis of the transmitted signal.

Claim 50. (New) The image pickup system according to claim 34, further comprising holding means for movably holding said video camera.

Claim 51. (New) The image pickup system according to claim 50, wherein said controlling means of said video camera moves said video camera by controlling said holding means on the basis of the command information from said commander.

Claim 52. (New) The image pickup system according to claim 34, wherein said plurality of operation modes includes an image pickup mode in which said image pickup means

picks up those images of an object which are recorded as image pickup signals to said recording means, and an edit mode in which the image pickup signals recorded earlier to said recording medium in said image pickup mode are edited.

Claim 53. (New) The image pickup system according to claim 52, wherein said image pickup mode includes a standby mode in which images based on the image pickup signals obtained by said image pickup means are displayed on said displaying means but in which said image pickup signals are not recorded to said recording medium, and a recording mode in which the images based on said image pickup signals obtained by said image pickup means are displayed on said displaying means and in which said image pickup signals are recorded to said recording medium.

Claim 54. (New) The image pickup system according to claim 34, wherein, in accordance with each of said plurality of operation modes, said controlling means accepts a specific part of the information received by said receiving means and ignores the remainder of the received information.

Claim 55. (New) The image pickup system according to claim 34, wherein said display device includes a microphone for generating an audio signal and transmitting means for transmitting said audio signal.

Claim 56. (New) The image pickup system according to claim 34, wherein said recording medium is a disk-type storage medium.

Claim 57. (New) The image pickup system according to claim 34, wherein said commander further includes a microphone for obtaining an audio signal.

Claim 58. (New) The image pickup system according to claim 34, wherein said video camera further includes an operation mode setting switch for setting one of said plurality of operation modes.

Claim 59. (New) An image pickup apparatus comprising:  
image pickup means for obtaining an image pickup signal by imaging an object; and  
receiving means for receiving a signal which is supplied from an external device and  
which includes command information; wherein said external device is a commander, having:  
command information storing means for storing a plurality of kinds of command  
information;  
command information generating means for generating a plurality of kinds of  
command information which correspond to a plurality of different operations performed  
by a user, the generation of the command information being carried out on the basis of  
said plurality of kinds of command information which are stored in said command  
information storing means;  
command transmitting means for transmitting said command information as  
transmitted information;  
recording and reproducing means for recording and reproducing said image  
pickup signal to and from a recording medium;

image information storing means for storing a plurality of kinds of image information; display-ready video signal generating means for generating a display-ready video signal by combining either of the image pickup signal obtained by said image pickup means or the image pickup signal reproduced from said recording medium by said recording and reproducing means and said image information;

signal transmitting means for transmitting said display-ready video signal; and

controlling means for controlling said image pickup means, said recording and reproducing means and said display-ready video signal generating means in accordance with any one of a plurality of operation modes.

Claim 60. (New) The image pickup apparatus according to claim 59, wherein said receiving means receives the signal transmitted over a wireless transmission line.

Claim 61. (New) The image pickup apparatus according to claim 59, wherein said image information storing means stores a plurality of kinds of image information constituting a graphic user interface capability.

Claim 62. (New) The image pickup apparatus according to claim 59, wherein, in accordance with the operation mode, said controlling means controls said display-ready video signal generating means to generate said display-ready video signal by use of different kinds of image information read from said image information storing means and said image pickup signal obtained by said image pickup means.



Claim 63. (New) The image pickup apparatus according to claim 59, wherein said plurality of operation modes include a standby mode in which images based on the image pickup signals obtained by said image pickup means are displayed on said displaying means but in which said image pickup signals are not recorded to said recording medium, and a recording mode in which the images based on said image pickup signals obtained by said image pickup means are displayed on said displaying means and in which said image pickup signals are recorded to said recording medium.

Claim 64. (New) The image pickup apparatus according to claim 63, wherein at least a part of said image information constitutes a graphic user interface capability which is not used in said recording mode but used in said standby mode.

Claim 65. (New) The image pickup apparatus according to claim 59, wherein said plurality of operation modes include a recording mode in which the images based on said image pickup signals obtained by said image pickup means are displayed on said displaying means and in which said image pickup signals are recorded to said recording medium and an edit mode in which the image pickup signals recorded on said recording medium are edited.

Claim 66. (New) The image pickup apparatus according to claim 65, wherein at least a part of said image information constitutes a graphic user interface capability which is not used in said recording mode but used in said edit mode.

Claim 67. (New) The image pickup apparatus according to claim 59, wherein said display-ready video signal generating means generates a pointer constituting part of said graphic user interface capability on the basis of said image information.

Claim 68. (New) The image pickup apparatus according to 59, wherein, in accordance with the operation mode, said controlling means controls said display-ready video signal generating means to generate said display-ready video signal by use of different kinds of image information read from said image information storing means as well as said image pickup signal obtained by said image pickup means.

Claim 69. (New) The image pickup apparatus according to claim 59, wherein said display-ready video signal generating means generates a pointer constituting part of said graphic user interface capability on the basis of said image information.

Claim 70. (New) The image pickup apparatus according to claim 69, wherein said controlling means moves said pointer within a frame on the basis of the signal received by said receiving means.

Claim 71. (New) The image pickup apparatus according to claim 70, wherein, after said receiving means has received a signal including a predetermined command transmitted from said external device, said controlling means moves said pointer only unidirectionally on the basis of the transmitted signal.

Claim 72. (New) The image pickup apparatus according to claim 59, wherein said plurality of operation modes include an image pickup mode in which said image pickup means picks up those images of an object which are recorded as image pickup signals to said recording means, and an edit mode in which the image pickup signals recorded earlier to said recording medium in said image pickup mode are edited.

Claim 73. (New) The image pickup apparatus according to claim 72, wherein said image pickup mode includes a standby mode in which images based on the image pickup signals obtained by said image pickup means are displayed on said displaying means but in which said image pickup signals are not recorded to said recording medium, and a recording mode in which the images based on said image pickup signals obtained by said image pickup means are displayed on said displaying means and in which said image pickup signals are recorded to said recording medium.

Claim 74. (New) The image pickup apparatus according to claim 59, wherein, in accordance with each of said plurality of operation modes, said controlling means accepts a specific part of the information received by said receiving means and ignores the remainder of the received information.

Claim 75. (New) The image pickup apparatus according to claim 59, wherein said recording medium is a disk-type storage medium.

Claim 76. (New) The image pickup apparatus according to claim 59, further comprising an operation mode setting switch for setting one of said plurality of operation modes.